## MINERAL SURVEY No. 3911

	Arizona Land D	istrict.
	FIELD NOTES	
	OF THE SURVEY OF THE MINING CLAIM OF	r
	The Arizona Copper Company	
	KNOWN AS THE	
	KEYSTONE NO. 6 EXTENSION lode.	
****	Copper Mountain	Mining District,
	Greenlee County, Arizona	•
lections 7	and 8 , Township 4 S. R. 29 E. , Rang	ge 29 E.
Surveye	ed under instructions dated September 5,	19 23
	hu Ol N. So	Terro
	UU	. S. Mineral Surveyor.
	Claim located See location notice	, 19
	Survey commenced September 17	, 19 23
	Survey completed September 18	, 19 23
J	Address of claimant J.P. Hodgson, Agt. and Att	ty in fact.
	DATES OF AMENDED LOCATIONS.	

Feet

MINERAL SURVEY NO. 3911

KEYSTONE NO. 6 EXTENSION LODE.

Beginning at Cor. No.1, identical with Loc. Mon.

A pine post 4 ins. sq. by 4 ft. high, set firmly in the ground and surrounded with md. of stone 3 1/2 ft. base by 3 ft. high, scribed 1-K 6 Ex.-3911, whence the Cor. to Secs. 5-6-7 and 8 T. 4 S., R 29 E. brs. N. 4° 43' W., 454.2 ft.

No other bearings are available.

Thence S. 34° 37' E. Va. 13° 30' E.

294.85

To E. end center.

An oak post 4 ins. diam. by 4 ft. high, set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high,

scribed E. Cr. K. 6 Ex.
Cor. No. 1 Sur. No. 1867 Shoo Fly lode, claimant unknown, and Intersect line 4-1 Sur. No.3346 Merriam lode, claimant unknown

at S. 77°36'E., 663.25 ft. from Cor. No.1 and N. 77°36'W., 815.81 ft. from Cor. No.4, also at Cor. No.1 Sur. No.1867 Shoo Fly lode, claimant unknown.

589.70

To Cor. No.2, identical with Loc. Mon. and Cor. No.2 Sur. No. 2859 Los Tajos lode, on line 1-2 Sur. No.1867 Shoo Fly lode. at S. 34°57'E. 74.2 ft. from Cor. No.1

A quartzite rock 6 x 12 x 12 ins. above ground, set 12 ins in the ground, chiseled with cross (x) 2-L T,2859, 2-K 6 Ex-3911 with md of stone 3 1/2ft. base by 3 ft high alongside.

A quartzite rock in place 12 x 18 ins. flush with the ground chiseled cross (x) 2-LT-2859, 2-K6 Ex-3911 - Br. Brs N. 34°37'W.,61.6 ft.

No other bearings are available.

Thence S. 55° 07' W. Va. 13° 30' E.

1500.00

To Cor. No.3, identical with Loc. Mon. and Cor . Mos. 1-1, Sur. No. 2859 Palo Verde and Los Tajos lodes.

A porphyry rock 3 x 6 x 12 ins above ground, chiseled with cross (x) 1 PV, 1 IF -2859, 3 K 6 Ex-3911, with md of stone 3 1/2 ft. base by 3 ft. high alongside.

Feet. 53.67 90.24 294.85 589,70

#### MINERAL SURVEY NO 3911

#### KEYSTONE No.6 EXTENSION Lode .- Cont'd.

A porphyry rock 12 x 12 ins showing 3 ins above ground (in place) chiseled with cross (x) 1-1,2859, 3-3911 BR., brs S. 10° E. 9 ft.

No other bearings are available.

Thence N. 34° 37' W. Va. 13° 30' E.

Intersect line 1-2 Sur No. 3346 Keystone No. 10 lode at S. 3° 01' E.,

31.14 ft. from Cor. No. 12 and N. 3° 01' W., 568.86 ft. from Cor. No. 2.38 V-4

Intersect lines 4-1 Keystone Nos 10 and 6 lodes at S. 86° 59'W.,

3&4,

19.16 ft. from Cor. Nos. 2-4 respectively

2 & \ and N. 86°59' E., 1480.84 ft. from Cor Nos. & 1.

294.85 To W. end center.

An oak post 4 ins. diam by 4 ft. high set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft high. Scribed W. Cr. K 6 Ex.

589.70 To Cor. No.4, identical with Loc. Mon.

A pine post 4 ins. Sq by 4 ft. high set firmly in the ground and surrounded with md of stone 3 1/2 ft. base by 3 ft. high, scribed 4 K 6 Ex-3911

Cor. No. 4 Sur. No.3346 Gov. Taft lode brs. N. 85°37'30" E.,377.14 ft.

No other bearings are available.

Thence N. 55° 07' E. va. 13° 30' E.

330.71 To Cor. No. 3 Sur. No. 3346 Keystone No. 6 lode, on line 3-4 Sur. No. 3346 Perplexity lode at S. 86° 59' W. 109.3 ft. from Cor.

No. 3 and N. 86° 59' E. 490.7 ft. from Cor. No. 4. Cor. No.3 said feystone No.6 lode brs.N.3°01'7.,600 ft from Cor. No.4 said lode.

466.08 Intersect line 4-1 Sur. No. 3346 Gov. Taft lode at N. 1°31' E.,

237.87 ft. from Cor. No4 and S 1° 31'W., 1262.13 ft. from Cor. No.1,

Also intersect line 2-3 Sur. No.3346 Perplexity lode at N. 1° 31' E.,

71.69 ft. from Cor. No.3 and S. 1°31'W.,954.57 ft. from Cor. No.2.

1078.20 Intersect line 1-2 Sur. No. 3346 Merriam lode at N. 12°24'E.,41.56 ft. from Cor. No.1 and S. 12°24'W.,558.44 ft from Cor. No.2.

1209.19 Intersect line 2-3 Sur. No.3346 Gov. Taft lode at N. 1°31'E. 631.29

ft. from Cor. No.3 and S. 1°31' W.,868.71 ft. from Cor. No.2. Cor.No.4
Said Gov.Taft lode brs. S.86°59'W.,600 ft. from Cor.No.3 said lode

1500.00 To Cor. No.1, the place of beginning.

-2-

-- 20.306

#### MINERAL SURVEY NO. 3911

#### KEYSTONE NO. 6 EXTENSION Lode.

#### LODE LINE.

As near as can be determined from the present developments, the veint of the location embraced in this claim, extends as follows from its discovery point:

170 ft.S. 55°07'W., and 1350 ft. N. 55°07' E.

#### AREA.

Total area Keystone Extension Ho.6 lode	
Area in conflict with:- Sur. No.3346 Keystone No.10 lode	0.007
Sur. No.3346 Keystone No.6 lode	-2.026
Sur. No.3346 Perplexity lode	-0.089
Sur. NO.3346 Gov. Taft lode	5.968
Sur. No.3346 Merriam lode Sur.No.3346 Merriam lode Exclusive of its conflict with Sur. No.334	
Gov. Taft lode	2 587

The survey of the lode of this location is identical with the location as staked upon the ground.

#### LOCATION.

This survey is located in N.E.1/4 Sec. 7 and the N.W. 1/4 Sec.8, T. 4S., R. 29 E., G. & S. R. M.

#### ----000----

#### EXPENDITURE OF FIVE HUNDRED DOLLARS.

I certify that the value of the labor and improvements made upon, or for the benefit of the location embraced in said mining claim by the claimant or its grantors is not less than five hundred dollars and that said improvements consist of:

No.1 the discovery shaft on the center line 170 ft. from the center of line 3-4, 4x6 ft. 10 ft. deep.

Value \$100.00

No.2 A shaft, the center of which brs. from Cor. No. 3 N. 38° E., 480 ft., 6 x 6 ft. 34 ft. deep.

Value \$510.00

INSTRUMENT.

## MINERAL SURVEY NO. 3911 KEYSTONE NO.6 EXTENSION Lode-Cont'd.

This survey was made with a Gurley mountain transit, the courses were deflected from the true meridian as determined by direct Solar observations. The distances were measured with a 500 ft. steel tape.

The lode line of the location of this claim was run directly upon the ground, and the corners were established by running around the claim.

The Cor. to Secs. 5-6-7 and 8, T. 4 S., R. 29 E. is an iron pipe with brass cap on top, stamped S.5, S.6, S.7- S.8, T. \$ S., R.29 E.

Sur. No.3346 Keystone No.10, Keystone No.6, Perplexity, Gov. Taft, and Merriam lodes, all corners consist of pine posts properly set

and scribed with the number of the Cor. and the Survey.

I find all courses and distances to be correct as approved.

Sur. No.1867 Shoo Fly lode, Cor. No.1 consists of a md. of stone

with no markings except a bearing rock nearby.

Sur. No.2859 Los Tajos lode Cor. No.2 consisted of a md. of stone with a bearing rock nearby. I set a quartzite rock 6 x 12 x 12 ins. above ground in the exact position of the original corner and properly chiseled it with the number of the corner and the survey.

Cor. Nos. 1--1- Los Tajos and Palo Verde lodes consist of a porphyry rock properly set and chiseled with the number of the Cor. and the Sur. Line 1-2 Los Tajos lode fails to furnish the course as approved (N. 55°06 E.) and same is properly given in these field notes.

#### ADJOINING CLAIMS.

On the North by Sur. No.3346 Keystone No.6, Perplexity, Gov. Taft and Merriam lodes.

On the East by Sur No. 3346 Merriam lode and Sur. No. 1867 Shoo Fly lode. On the South by Sur. No. 2859 Los Tajos lode, and on the West by Sur. No. 3346 Keystone Nos. 6 and 10 lodes.

#### MINERAL SURVEY No. 3911

#### KEYSTONE No.6 EXTENSION Lode.

#### SOLAR OBSERVATION.

Direct Solar Observation taken Monday September 17, 1923 at 2:13 P.M. Solar time . Sun bisected, Lat. 33° 06'. Lon. 109°23'

Difference in time 9h 30'

Apparent declination 2° 33' 30" / 9' 10" / 2° 24' 20" /

P = 90°- Dec'1 = 87°35'40"/

L=33° 06'
H=46° 28'
P=87° 35' 40"
2)167° 09' 40"
S= 83° 34' 50"

Sin 1/2 A =  $\sqrt{\frac{\text{Sin (S-L) (S-H)}}{\text{Cos L Cos H}}}$ 

S-L = 50° 28' 50" 9.8872845 9.7806062

9.8872845 9.7806062 0.0769018 0.1619217 2) 19.9067142 9.9533571 = 63° 55' = 1/2 A

127° 50' = A

180°- 127°50' = S.52° 10'W. $\sqrt{\phantom{0}}$  = Course of sun. 2° 57' = Ang. to right from Sun. S.55° 07'W. $\sqrt{\phantom{0}}$  = Course of line.

Set up at Cor. No.2 F.S. to Cor. No.3

## FINAL OATHS FOR SURVEYS.

### LIST OF NAMES.

A list of the names o	the individuals employed by <u>T. N. Stevens</u>
United States Mineral St	rveyor, to assist in running, measuring, and marking the lines, corners, and
	e foregoing field notes of the survey of the mining claim of
	The Arizona Copper Company
	KEYSTONE NO. 6 EXTENSION Lode
	capacities in which they acted.
	John H. Dexter , Chainman.
	, Chainman.
	, Axman.
	, Asman., Asman.
	, Flagman.
FI	NAL OATHS OF ASSISTANTS.
	xter
	, do solemnly swear that we assisted
	, United States Mineral Surveyor, in marking the corners and surveying
	ng claim of The Arizona Copper Company
	KEYSTONE No.6 EXTENSION Lode.
	g field notes as having been surveyed by said mineral surveyor and under his
	vey has been in all respects, to the best of our knowledge and belief, faithfully
	he corner and boundary monuments established according to law and the instruc-
ions furnished by the Unite	States Surveyor-General for Arizona.
	John H. Dester, Chainman.
	Chainman.
	, Axman,
	, Flagman
Subscril	ed and sworn to by the above-named persons before me this
da	of Deleuher, 1923
My Com	nission Expires June 4, 1994 Sakel M. Lauder
	Workers Tublic

## FINAL OATH OF U.S. MINERAL SURVEYOR.

I, T. N. Stevens	, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of in	
Surveyor General for Arizona	
September 5 1923 , , I	have, in strict conformity to the laws of the
United States, the official regulations and in	nstructions thereunder, and the instructions
of said Surveyor General, faithfully and co	
Claim of The Arizona Copper Company	
KEYSTONE NO.6 EXTENSION Lode	
situate in Copper Mountain	
Greenlee Co	ounty, Arizona in Sections
7 and 8 , Township No. 4 S. , Rang	ge No. 29 E., G. & S. R. M.
and designated as Survey No. 3911	
in the foregoing field notes, which accurately	
as distinctly marked by monuments on the g	
of the location certificate, which was receive	
said instructions, and that all the corners of	
petuated in strict accordance with the law,	
under; and I do further solemnly swear tha	
field notes of said survey and my report t	
improvements made upon said mining claim	
are as therein fully stated, and that the cha	
thereof are specified therein with particulari	
said labor or improvements so credited to the	
of o	
	MN & Xerrus
	U. S. Mineral Surveyor.
	01 11
Subscribed and sworn to by the said	7/1. Stevens
U. S. Mineral Surveyor, before me	abel M. Jauder
a Hostary Tublic	this 6
day of Mellewker, 1923	
My Commission Expires June 4, 1984	Loon P
	sake Mi auder
5—1044	Motary tuble

### U. S. SURVEYOR GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

DEPARTMENT OF THE INTERIOR, OFFICE OF U. S. SURVEYOR GENERAL,

Phoenix, Arizona,
February 25 , 1924.
I, U. S. Surveyor General for District of Arizona
do hereby certify that the foregoing transcript of the Field Notes, return and approval
of the Survey of the mining claim of
The Arizona Copper Company
, known as the KEYSTONE NO. 6 EXTENSION lode
, situate in Copper Mountain
Mining District, Greenlee County,
, in Section s 7 and 8 , Township No. 4 S.,
Range No. 29 E. , and designated as Survey
No. 3911 , has been correctly copied from the originals on file in this office; that said Field Notes furnish such an accurate description of said mining claim as will, if incorporated into a patent, serve fully to identify the premises, and that such reference is made therein to natural objects or permanent monuments as will perpetuate and fix the locus thereof.  And I further certify that five hundred dollars' worth of labor has been expended or improvements made upon said mining claim by claimant or 1ts grantors, and that said improvements consist of 2 shafts, total value \$610.
and that no portion of said labor or improvements has been included in the estimate of expenditures upon any other claim.  I further certify that the plat thereof, filed in the U.S. Land Office at Phoenix,  Arizona. is correct and in conformity with the foregoing Field Notes.
Charles M. Donahoe
United States Surveyor General for Arizona.

# SURVEYOR GENERAL'S CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

### DEPARTMENT OF THE INTERIOR

OFFICE OF U. S. SURVEYOR GENERAL

Phoenix, Arizona,
February 25 , 192
I, U. S. Surveyor General for District of Arizona
do hereby certify that the foregoing and hereto attached Field Notes and Return of the Survey of the
Mining Claim of
The Arizona Copper Company
, known as the
KEYSTONE NO. 6 EXTENSION lode
situate in mining district,
Greenlee County, Arizona
in Sections 7 and 8 , Township No. 4 S., Range No. 29 E.
, designated as Survey No3911
executed by, U. S. Mineral
Surveyor,September 17 - 18, 1923, under my instructions dated
September 5, 1923, have been critically examined and the necessary
orrections and explanations made, and the said Field Notes and Return, and the survey they describe,
are hereby approved. The certified copy of the location certificate filed by the applicant for survey is
n file in this office and a true copy of said certified copy of said location certificate is included and
nade a part of the transcript of the field notes.

Tearles M. Donohoe.

U. S. Surveyor General for Arizona